Biowood
Sustainably Reconstituted Timber

"Green isn't just a colour... it is the future"

Architectural Decking

Why you should choose Biowood...

- Lightweight and durable
- Termite resistant
- Fire & water resistant
- Mould & mildew resistant
- Can be re-sanded & re-sealed
- No splinters, cracks or rot
- Easy installation
- A proven time tested product in Australia, ideal for residential & commercial application
- Trusted brand by Global Green Tag

FIND US ON globalgreentag.com

ecospecifier global GREEN TAG CERTIFIED

trust brands

Scan this code for more information

water Resistant

GRM

Green Resources Material Australia Pty Ltd

biowoodaustralia.com.au | +61 2 9644 6766

Biowood
Sustainably Reconstituted Timber

"Green isn't just a colour... it is the future"

FIND US ON globalgreentag.com

ecospecifier global GREEN TAG CERTIFIED

trust brands

Scan this code for more information

Retaining the natural timber look, low maintenance and environmentally friendly.

Architectural Decking

Biowood wood composite products are created using 0.85 density natural cellulose fibre from plantation harvested wood, and combined with resin.

Fire Resistant - AS 1530.3 CSIRO Test Report: self-extinguishing – has a Spread of Flame Index of ZERO (0) and Heat Evolve Index of ONE (1). Unlike solid timber, it will not continue burning when the source of heat is removed. Only Merbau/Kwila and White Mahogany have similar properties.

Labour Efficient - Easy installation, concealed fixing, lighter than other materials, less manpower needed, long lengths, straight and true to shape and size, use standard carpentry tools

Durable - water, mould, mildew, termite resistant; will not splinter, crack or warp; proven, time tested suitability for marine, intertidal and salt spray environments, UV Stable under normal environmental conditions, even in full sun, when coated with Biowood water based coating

Environmentally Friendly - fully recyclable, also suitable for indoor environments – very low volatile compounds emissions at an E1 Rating

Cost Effective - Serviceable Life Warranty – will perform for the serviceable life of the building when installed in accordance with the methods described

Product Warranty – 15 years from date of purchase, to be free from manufacturing defects and/or faulty material, provided they are properly installed and maintained

Virtually maintenance free – depending on north orientation coating will last for 3 times longer than normal UV coating.

GRM Green Resources Material Australia Pty Ltd biowoodaustralia.com.au | +61 2 9644 6766